Empowered by Innovation

NEC

LCDs • Projectors • Plasmas • LCDs • Projectors • Plasmas • LCDs • Projectors

PlasmaSync® 60XC10

see more.

NEC Display Solutions

Stylish Plasma Public Displays for multimedia applications and design oriented installation purposes.

- Stylish design
- 60" WXGA resolution
- HDMI and DVI with HDCP support
- Overheating protection
- 1080p and 24p compatible

PlasmaSync® 60XC10

TECHNICAL SPECIFICATIONS

Screen Size [inch/cm]	60/152.4
Native Resolution (H x V) [Pixel]	1366 x 768
Screen Size (H x V) [mm]	1320 x 742
Aspect Ratio	16:9
Viewing Angle	Over 160°
Contrast (typ.)	10000:1
Panel Brightness (typ.) [cd/m²]	1200
Real Colour Reproduction	1 billion colours, 1024 steps (10 bit)
Digital Zoom	100 - 900 % (selectable)
Picture Modes	Bright / Normal / Cinama1 / Cinema2 / Default
Enhanced Split Screen	PIP (4 modes), Side by Side (6 modes), Sub Picture Detect / Fade / Transparency
Motion Compensated 3D Scan-Converter	PAL, NTSC, 480i, 576i, 525i, 625i, 1035i, 1080i
Complete Progressive Support	480p@60Hz, 576p@50Hz, 720p@50/60Hz, 1080p@24/25/30/50/60Hz, PC: W-UXGA (1920 x 1200 max)
Noise Reduction	NR-1, NR-2, NR-3
Aspect Mode	Normal, Full, Dynamic, Zoom, 2,35:1, 14:9, Underscan
PDP Screensaver	PLE (3 modes), Inverse, White, Orbiter (5 modes)
Tuner	Optional
Composite 1	RCA x 1
Composite 2	-
S-Video	4 pin DIN x 1
SCART 1	RGBs (via Adapter at DVD/HD1)*
SCART 2	RGBs (via Adapter at RGB)*
Component 1	RCA (Y, Pb[Cb], Pr[Cr]) x 1*
Component 2	RCA (Y, Pb[Cb], Pr[Cr]) x 1
PC (RGB)	15 pin D-Sub (RGBHV/RGBs) x 1*
DVI-D / HDMI	DVI-D (HDCP) x 1 / HDMI x 1
Audio 1	RCA Phono (L+R) x 1
Audio 2	RCA Phono (L+R) x 1
Audio 3	RCA Phono (L+R) x 1
Speaker Output	8 + 8 W at 8 Ohm
Front Panel User Controls	Power ON/Standby, Audio Mute, Input Select/(Set), +/(Right), -/(Left), Up, Down, Exit/Menu
Serial Communication	D-Sub 9 pin Serial x 1 (RS-232C, In/Out); Daisy Chain; AMX Cafè Duet
Power Source	100 to 240 V at 50/60Hz
Power Consumption (typ.) [W]	440
Current Rating (max.) [A]	7.0
Dimensions (W x H x D)	1470 x 880 x 122
Net Weight [kg]	Without stand: 70.0; With stand: 85.0
Temperature	0ºC to 40ºC (operation) / -10ºC to 50ºC (storage)
Humidity	20 % to 80 % (operation) / 10 % to 90 % (storage) – no condensation
Altitude	0 to 2000 m (6160 feet, operation) / 0 to 3000 m (9510 feet, storage)
Options	Speakers, stand
Special Features	3D Scan Converter, 3-2/2-2 Pulldown Converter, Digital Zoom, Burn In Reduction Tools, Auto Picture, Colour Tune, Gamma Correction, Auto Luminance Management, Remote-ID up to 26 devices, Overheating protection

*DVD/HD1 and RGB inputs support different signals.

PlasmaSync® and OSM are registered trademarks of the NEC Corporation. The plasma display screen, also called „panel", is comprised of tiny image elements (cells). Although NEC manufactures these plasma displays with 99.99 % of their cells active, individual cells may occasionally produce no light or remain lit when they should have turned off. The brightness of a plasma display declines during the course of the unit's lifetime. Static images should not be displayed over a longer period of time, as this may cause phosphor burn on certain areas of the screen. Phosphor burn is not covered by the warranty. Please note our terms and conditions of our guarantee at www.nec-display-solutions.com Status: November 2007. Technical modifications excepted.

Plasma 60XC10-UK-11/07

www.nec-display-solutions.com
NEC Display Solutions UK Ltd, 32 Southwark Bridge Road, London SE1 9EU
Phone: 0207 202 6300, e-mail: infomail@nec-displays.com - For further information on NEC products call: 08701 201160